

THE CRAFTSMAN CHOICE



**SUPER  
2000**

# WOOD VARNISH

SOLVENT BASE  
HIGH GLOSS TRANSPARENT FINISH



## DESCRIPTION

Super 2000 Wood Varnish is a general purpose varnish for interior & exterior use. Suitable for protection of wooden surfaces where a gloss finish is required.

## USES

- Wooden Fascias & Knotty Pine Paneling & Ceilings
- Wooden Doors, Window Frames, Skirting Boards & Indoor/Outdoor Furniture.

## BENEFITS

- All-Weather Protection
- Durable Glossy Finish
- Apply with Paintbrush / Roller
- Interior & Exterior Use
- Quality Guaranteed

## APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, & allow overnight drying time between coats. Clean tools (paintbrushes) with Mineral Turpentine immediately after use

## COLOUR RANGE

Available in standard colours

## SPREADING RATE

This product will cover approximately 6-8m<sup>2</sup>/litre, depending on surface porosity

## SURFACE PREPARATION

**NEW SURFACES:** Surface/s must be thoroughly clean, dry & in sound condition before painting.

Sand surface (in the direction of the wood grain) to a smooth finish, & remove dust with a cloth. Apply one coat of Sanding Sealer (if applicable), followed by two coats of Super 2000 Wood Varnish. Allow overnight drying between coats. For best results, sand lightly between coats in the direction of the wood grain.

**PREVIOUSLY VARNISHED OR PAINTED SURFACES:** Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint or varnish. Sand lightly to a smooth finish. Apply two coats of Super 2000 Wood Varnish, & allow overnight drying between coats. For best results, sand lightly between coats in the direction of the wood grain. Painted surfaces must be stripped back to bare wood than follow the "Instructions for Use" as described under New Surfaces.

**WARNING:** This product is not suitable for use on Wooden Floors, Gumpoles or Timber Fencing.

**PRECAUTIONS:** Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

**QUALITY GUARANTEE:** This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

## TECHNICAL DATA

TYPE	Solvent
FINISH	Gloss
DRYING TIME @ 25°C	Touch Dry: 4 Hours
RE-COATING TIME	16 Hours
VISCOSITY	68/72 Kp
WASH ABILITY	
PACK SIZE	250ml / 1Lt / 5Lt

# PRODUCT DATA SHEET

