

Luxurious Touch

PLATINUM
SERIES

SUPER ENAMEL GLOSS

INTERIOR/EXTERIOR
DURABLE - HIGHLY WASHABLE - HARD WEARING



DESCRIPTION

Platinum Super Enamel Gloss is a superior quality paint suitable for decorating & protecting all interior & exterior surfaces. This product has an excellent gloss level, fully washable, & it can be applied to a variety of surfaces where a long-lasting glossy finish is required

USES

- New & previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster
- Primed Metal & Wooden Surfaces
- Ideal for Steel Door & Window Frames; Kitchen & Bathroom Walls; Gates; Steel Fencing; Skirting Boards & Garden Furniture etc

BENEFITS

- Excellent Durability
- Stain & Dirt Resistant
- Good Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, & allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use

COLOUR RANGE

Available in white & standard colours

SPREADING RATE

This product will cover approximately 8-10m²/litre, depending on surface porosity

TECHNICAL DATA

TYPE	Solvent
FINISH	High Gloss
DRYING TIME @ 25°C	Touch Dry: 4 Hours
RE-COATING TIME	16 Hours
VISCOSITY	70/80 Kp
WASHABILITY	Excellent
PACK SIZE	250ml / 500ml / 1Lt / 5Lt / 20Lt

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before commencing work

GALVANISED IRON: Clean & remove all oil/grease prior to applying one coat of Steel Primer. Apply two coats of Platinum Super Enamel Gloss

IRON & STEEL: Clean & remove all grease & rust. Apply one coat of Solvent Etch primer, followed by one coat of Universal Undercoat & two coats of Platinum Super Enamel Gloss

CONCRETE / CEMENT PLASTER: Apply one coat of Plaster Primer, followed by one coat of Universal Undercoat. Apply two coats of Platinum Super Enamel Gloss

TIMBER/WOOD: Sand surface to a smooth finish. Apply one coat of Pink Wood Primer, followed by one coat of Universal Undercoat & two coats of Platinum Super Enamel Gloss

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Spot prime all bare areas with the correct primer, followed by one coat of Universal Undercoat & two coats of Platinum Super Enamel Gloss

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

