

Luxurious Touch

PLATINUM
SERIES

MARBLE TEXTURE

INTERIOR/EXTERIOR
FINE TEXTURED - WEATHER RESISTANT - EXTREMELY DURABLE



DESCRIPTION

Platinum Marble Texture is a flexible exterior wall coating, which is recommended for use on exterior concrete & cement-plastered surfaces. This product contains Mica for stretch. It covers all hairline cracks, & it has excellent alkali & water-resistant properties to withstand the harshest climatic conditions. Also suitable on other areas where a fine durable matt textured finish is required

USES

- New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork & Gypsum Plaster
- Asbestos/Fibre Cement Boards
- Primed Metal & Wooden Surfaces
- Ideal for Exterior Walls

BENEFITS

- Pure Acrylic Paint
- Excellent Elasticity
- Hides Hairline Cracks
- Excellent UV Resistance
- Apply with Brush or Roller
- Ideal for Exterior Surfaces
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile/ lambswool / foam) paint roller, & allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use

COLOUR RANGE

Available in white, standard colours

SPREADING RATE

This product will cover approximately 5-7m²/litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

TYPE	Acrylic
FINISH	Matt
DRYING TIME @ 25°C	Touch Dry: 30 Minutes
RE-COATING TIME	4 Hours
VISCOSITY	
WASH ABILITY	
PACK SIZE	5lt / 20lt

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before painting

CONCRETE/CEMENT PLASTER: Apply one coat of Plaster Primer, followed by two coats of Platinum Marble Texture

ASBESTOS/FIBRE CEMENT: Apply one coat of Plaster Primer, followed by two coats of Platinum Marble Texture

IRON & STEEL: Apply one coat of Steel Primer, followed by one coat of Universal Undercoat & two coats of Platinum Marble Texture

TIMBER/WOOD: Sand surface to a smooth finish. Apply one coat of Pink Wood Primer, followed by one coat of Universal Undercoat & two coats of Platinum Marble Texture

GYPSUM PLASTER (RHINOLITE/RHINOGLIDE): Apply one coat of Plaster Primer, followed by two coats of Platinum Marble Texture

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Powdery surfaces must be treated with one coat of Plaster Primer prior to applying two coats of Platinum Marble Texture

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

