



CEILING PAINT

ACRYLIC BASE - INTERIOR/EXTERIOR
QUICK DRYING - GOOD CAPACITY - MATT FINISH



DESCRIPTION

Home Ceiling Paint is a superior quality Acrylic Pva, which has been formulated for interior & exterior ceilings. This product has excellent hiding power properties. It can be applied to ceilings made from different surfaces where a durable smooth matt finish.

USES

- Suitable for Internal & External Ceilings made from Cement Plaster, Concrete & Gypsum Plaster

BENEFITS

- Quick Drying
- Good Opacity
- Smooth Matt Finish
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furple / lambswool) paint roller, & allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use

COLOUR RANGE

White

SPREADING RATE

This product will cover approximately 6 - 8m²/litre, depending on surface porosity

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before commencing work

ASBESTOS/FIBRE CEMENT: Apply one coat of Plaster Primer, followed by two topcoats of Home Ceiling Paint. Allow sufficient drying time between coats

GYPHUM PLASTER (RHINOLITE/RHINOGLIDE): Apply one coat of Plaster Primer, followed by two topcoats of Home Ceiling Paint

PREVIOUSLY PAINTED SURFACES: Surface/s in poor condition such as Powdery/Chalked

PVA / LIME-WASH: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Apply one coat of Bonding Liquid, followed by one coat of Universal Undercoat (if necessary) & two topcoats of paint in the desired finish

CEMENT PLASTER: Apply one coat of Plaster Primer, followed by two coats of Home Ceiling Paint. Alternatively, apply one thin coat of Home Ceiling Paint, followed by two coats un-thinned

TIMBER/WOOD: Apply one coat of Pink Wood Primer, followed by one coat of Universal Undercoat & two coats of Home Ceiling Paint

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Apply two coats of Home Ceiling Paint direct to the surface. Powdery surfaces must be treated with one coat of Plasterbond, prior to applying two coats of Ceiling Paint. Enamel based surfaces must be cleaned & prepared correctly. Sand lightly & apply one coat of Universal Undercoat, followed by two coats of Ceiling Paint.

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

TECHNICAL DATA

TYPE	Acrylic
FINISH	Matt
DRYING TIME @ 25°C	Touch Dry: 30 Minutes
RE-COATING TIME	4 Hours
VISCOSITY	100/110 K μ
WASH ABILITY	
PACK SIZE	5Lt / 20Lt

PRODUCT DATA SHEET

