



TOUGH ROOF & PAVE

ACRYLIC BASE - INTERIOR/EXTERIOR
BUILT FOR EXTREME WEATHER



DESCRIPTION

Home Tough Roof & Pave is an all weather-resistant pure acrylic paint with a low sheen finish, which has been developed to provide good durability. This product is suitable for Asbestos Cement Roof Sheets or Tiles, Cement or Clay Roof Tiles & on Primed Galvanised Iron Roofs & Concrete Pavings.

USES

- Roof Tiles - Concrete Pavings
- Concrete Window Sills
- Asbestos/Fibre Cement surfaces such as Facia Boards Garden Pots; Gutters & Downpipes
- Primed Metal & Wooden Surfaces

BENEFITS

- Pure Acrylic Paint
- Excellent UV Resistance
- Apply with Brush or Roller
- Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08,00-11,00 hrs & again from 15,00-18,00 hrs. Apply this product with a paintbrush or (furpile / lambswool) paint roller, & allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use

COLOUR RANGE

Available in white & standard colours

SPREADING RATE

This product will cover approximately 5-7m²/litre, depending on surface porosity

TECHNICAL DATA

TYPE	Pure Acrylic
FINISH	Mid Sheen
DRYING TIME @ 25°C	Touch Dry: 30 Minutes
RE-COATING TIME	4 Hours
VISCOSITY	95 - 108 Kp
WASH ABILITY	
PACK SIZE	1Lt / 5Lt / 20Lt

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before painting

GALVANISED STEEL: Clean & remove all manufacturers pre-treatment (oil/grease), prior to applying one coat of Steel Primer, followed by two coats of Home Tough Roof & Pave

IRON & STEEL: Remove all grease & surface rust before painting. Apply one coat of Red Metal Primer, followed by two coats of Home Tough Roof & Pave

CEMENT ROOF / NUTEC TILES: Apply the first coat thinned with 10% water to aid penetration, followed by two coats of Home Tough Roof & Pave un-thinned.

ASBESTOS/FIBRE CEMENT: Apply one coat of Plasterbond, followed by two coats of Home Tough Roof & Pave

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Powdery surfaces must be treated with one coat of Plasterbond prior to applying two coats of Home Tough Roof & Pave applied unthinned. Ensure the surface is correctly prepared before commencing to paint.

WARNING: Avoid painting if the roof is too hot or covered with mildew, which means that the recommended times to paint may vary as indicated under application

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

