



ACRYLIC PVA

INTERIOR & EXTERIOR



DESCRIPTION

Master Coat is a acrylic based PVA developed for interior & exterior surfaces. This product has high coverage & filling properties.

USES

- New & previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster
- Asbestos/Fibre Cement Fascias & Ceiling Boards
- Primed Metal & Wooden Surfaces
- Ideal for Interior & Exterior Walls

BENEFITS

- Good Hiding Power
- Multi-Purpose Use
- Interior / Exterior
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furple / lambswool) paint roller, & allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use

COLOUR RANGE

Available in white & standard colours

SPREADING RATE

This product will cover approximately 6-8m²/litre, depending on surface porosity

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before painting

CONCRETE/CEMENT PLASTER: Apply one coat of Home Plaster Primer, followed by two coats of Master Coat

ASBESTOS/FIBRE CEMENT: Apply one coat of Plaster Primer, followed by two coats of Master Coat

IRON & STEEL: Apply one coat of Steel Primer, followed by one coat of Universal Undercoat & two coats of Master Coat

TIMBER/WOOD: Apply one coat of Pink Wood Primer, followed by one coat of Universal Undercoat & two coats of Master Coat

GYPHUM PLASTER (RHINOLITE/RHINOGLIDE): Apply one coat of Plaster Primer, followed by two coats of Polo

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Powdery surfaces must be treated with one coat of Plasterbond, prior to applying two coats of Master Coat. Enamel based surfaces must be cleaned & prepared correctly. Sand lightly & apply one coat of Universal Undercoat, followed by two coats of Master Coat

TECHNICAL DATA

TYPE	Acrylic
FINISH	Matt
DRYING TIME @ 25°C	Touch Dry: 15 Minutes
RE-COATING TIME	50 Minutes
VISCOSITY	110 Kp
WASH ABILITY	
PACK SIZE	5Lt / 20Lt

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

