

# INDUSTRIAL RANGE

## ALUMINIUM SILVER



### DESCRIPTION

Africa Paints Aluminium Silver will reflect heat & reduce the overall temperature of a home or building. This product is primarily used to protect Galvanised Iron Roofs, Steel Fencing, Posts & Gates & on other areas where a durable silvery finish is required

### PRODUCT USES

- Metal & Galvanised Iron Surfaces

### PRODUCT BENEFITS

- Quick Drying
- Good Adhesion Properties
- Excellent Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller, & allow 30 Minutes drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use

### SPREADING RATE

This product will cover approximately 6-8m<sup>2</sup>/litre, depending on surface porosity.

### SURFACE PREPARATION

**NEW SURFACES:** Surface/s must be thoroughly clean, dry & in sound condition before painting

**IRON & STEEL:** Remove oil/grease & surface rust before painting. Apply one coat of Solvent Etch Primer, followed by two coats of Aluminium Silver

**GALVANISED IRON:** Clean & remove all oil/grease with Galvanised Iron Cleaner, prior to applying one coat of Steel Primer, followed by two coats of Aluminum Silver

**ASBESTOS/FIBRE CEMENT:** Apply one coat of Bonding Liquid, followed by two coats of Aluminum Silver

**PREVIOUSLY PAINTED SURFACES:** Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Spot prime all bare areas with the appropriate primer before applying two coats of Aluminium Silver

**NOTE:** This product is suitable for spray application

### TECHNICAL DATA

TYPE	Solvent
FINISH	Silver
DRYING TIME @ 25°C	Touch Dry: 4 Hours
RE-COATING TIME	16 Hours
WASH ABILITY	
PACK SIZE	1Lt / 5Lt

**PRECAUTIONS:** Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

**QUALITY GUARANTEE:** This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

# PRODUCT DATA SHEET

