

# INDUSTRIAL RANGE

## BONDING LIQUID



### DESCRIPTION

Africa Paints Bonding Liquid is a solvent-based primer & sealer, which has been specially formulated to provide excellent penetrating properties for adhesion to very powdery & porous surfaces for interior & exterior use.

It can also be used to bind Powdery/Chalked Pva or Lime Wash to the original surface

### USES

- Suitable for sealing very porous surfaces such as Asbestos/Fibre Cement & Gypsum Plaster
- Binding Powdery/Chalked Pva or Lime Washed surfaces

### BENEFITS

- Primer & Sealer
- Excellent Binding Properties
- Ideal for Chalked Pva Surfaces
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

### APPLICATION

Stir the contents thoroughly before use This product should be applied without thinning. If thinning is required use Mineral Turpentine. Apply this product with a paintbrush or (mohair) paint roller, & allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use

### COLOUR RANGE

Clear finish

### SPREADING RATE

This product will cover approximately 10-15m<sup>2</sup>/litre, depending on surface porosity

### SURFACE PREPARATION

**NEW SURFACES:** Surface/s must be thoroughly clean, dry & in sound condition before commencing work

**ASBESTOS/FIBRE CEMENT:** Apply one coat of Bonding Liquid, followed by two topcoats of paint in the desired finish & colour. Allow sufficient drying time between coats

**GYPSUM PLASTER (RHINOLITE/RHINOGLIDE):** Apply one coat of Bonding Liquid, followed by two topcoats of paint in the desired finish & colour

**PREVIOUSLY PAINTED SURFACES:** Surface/s in poor condition such as Powdery/Chalked

**PVA / LIME-WASH:** Thoroughly clean & prepare surface by removing all dirt, grease, grime & flaking paint before painting. Apply one coat of Bonding Liquid, followed by one coat of Universal Undercoat (if necessary) & two topcoats of paint in the desired finish

### TECHNICAL DATA

TYPE	Solvent
FINISH	Clear
DRYING TIME @ 25°C	Touch Dry: 40 Minutes
RE-COATING TIME	12 Hours
VISCOSITY	15 - 25 Sec FC4 Cup @ 25°C
WASH ABILITY	
PACK SIZE	1Lt / 5Lt

**PRECAUTIONS:** Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C  
 • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

**QUALITY GUARANTEE:** This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

# PRODUCT DATA SHEET

