

INDUSTRIAL RANGE

PINK WOOD PRIMER



DESCRIPTION

Africa Paints Pink Wood Primer is an oil-based wood primer, which is primarily used to protect all interior & exterior timber surfaces. This product has excellent filling & sealing properties & is normally as an undercoat, product needs to be painted thereafter with a suitable topcoat.

BENEFITS

- Good Adhesion Properties
- Excellent Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. If thinning is required use Mineral Turpentine. Apply this product with a paintbrush or (Mohair) paint roller, & allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use

COLOUR RANGE

Pink

SPREADING RATE

This product will cover approximately 8-10m²/litre, depending on surface porosity

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before commencing work

Sand the surface to a smooth finish. Apply one coat of Africa Paints Pink Wood Primer, followed by one coat Universal Undercoat, & two final coats in the appropriate paint finish.

TECHNICAL DATA

TYPE	Solvent
FINISH	Finish Matt
DRYING TIME @ 25°C	Touch Dry: 40 Minutes
RE-COATING TIME	16 Hours
VISCOSITY	72 - 77 Kp
SPECIFIC GRAVITY	1.14 kg / litre
PACK SIZE	1Lt / 5Lt

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C
• Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

