

INDUSTRIAL RANGE

QUICK DRYING ENAMEL



DESCRIPTION

Africa Paints Quick Drying Enamel is a high quality paint suitable for the protection & decoration of all interior & exterior steel surfaces where a durable glossy finish is required

USES

- Interior & Exterior Furniture
- Truck Parts & Tractors
- Plant & Machinery

BENEFITS

- Good Durability
- Long Lasting Finish
- Excellent Hiding Power
- Apply with Brush, Roller or Spray
- Interior & Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied as described under Surface Preparation. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush (small areas), paint roller or conventional spray, & allow a minimum of 4 hours drying time between coats. Spray application: thin down as described above for use with standard high-pressure spray guns — air pressure 3-5 bar. Clean tools (brushes, rollers & spraying equipment) with Quick Drying Thinners immediately after use.

SPREADING RATE

This product will cover approximately 8-10m²/litre, depending on surface porosity

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before commencing work. Apply one coat of Africa Paints QD Industrial Primer, followed by two coats of Africa Paints QD Industrial Enamel thinned by 20% with Africa Paints Quick Drying (BA) Thinners. Allow 4 hours drying time between coats

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, grease grime & flaking paint before commencing work. Spot prime all bare areas with the appropriate primer, prior to applying two coats of Africa Paints QD Industrial Enamel

TECHNICAL DATA

TYPE	Solvent/Styrenated Alkyd
FINISH	Finish Gloss
DRYING TIME @ 25°C	Touch Dry: 10 Minutes
RE-COATING TIME	4 Hours
VISCOSITY	65/70 Kp
WASH ABILITY	
PACK SIZE	1Lt / 5Lt / 20Lt

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary • Wear protective clothing such as Overall, Gloves, Goggles etc

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

