

THE CRAFTSMAN CHOICE

africa
paints

SUPER
2000

STOEP PAINT

SOLVENT BASE
ALKALINE RESISTANT - CONCRETE SURFACES



DESCRIPTION

Super 2000 Stoep Paint is a premium alkali-resistant enamel based paint, which is primarily used to protect & decorate small concrete floors & window sills. This product is easy to apply & dries to a durable glossy finish

USES

- Suitable for Concrete Floors & Window Sills

BENEFITS

- Complete Protection
- Durable Glossy Finish
- Fully Washable
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, & allow 3 hours drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use

COLOUR RANGE

Available in standard colours

SPREADING RATE

This product will cover approximately 6-8m²/litre, depending on surface porosity

SURFACE PREPARATION

NEW SURFACES: Surface/s must be thoroughly clean, dry & in sound condition before painting

NEW SURFACES: Surfaces must be thoroughly clean, dry & in sound condition & free from polish or wax before painting. Newly laid concrete floors must be allowed to dry for 6 weeks. Smooth floors must be cleaned with hydrochloric acid & rinsed off with water, & allowed to dry before painting. Apply one coat of Super 2000 Stoep Paint thinned with 10% Mineral Turpentine, followed by two coats of Super 2000 Stoep Paint unthinned

PREVIOUSLY PAINTED SURFACES: Thoroughly clean & prepare surface by removing all dirt, wax, polish & flaking paint before commencing to paint. Rub down with sandpaper & ensure surface is dry & clean & in sound condition before applying two coats of Super 2000 Stoep Paint

WARNING: This product is not suitable for surfaces continually exposed to Oil / Grease or strong Solvents etc.

TECHNICAL DATA

TYPE	Solvent
FINISH	Gloss
DRYING TIME @ 25°C	Touch Dry: 4 Hours
RE-COATING TIME	16 Hours
VISCOSITY	80/85 Kp
WASH ABILITY	
PACK SIZE	500ml / 1Lt / 5Lt

PRECAUTIONS: Do not apply if rain is imminent • Apply at an ambient temperature lower than 35°C • Keep out of reach of children • Wash hands with Mineral Turpentine immediately after use • Skin or Eye contact: clean with fresh water and consult a physician if necessary.

QUALITY GUARANTEE: This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith & correct to the best of our knowledge, but Africa Paints reserves the right to change these specifications if deemed necessary.

PRODUCT DATA SHEET

